

## MultiCo EW-108

- \* Metal Case with Pocket Size
- \* Powered by PC USB Port
- \* Auto-MDI/MDI-X
- \* Auto-Negotiation
- \* Non-Blocking
- \* Store and Forward



### 8-port 10M/100M Mini Fast Ethernet Switch

#### Introduction

EW-108 are 8-port 10M/100M Mini Fast Ethernet Switch that is designed for small or medium network environment to strengthen its network connection. This product is easy to install and use and can be powered by PC USB port. It provides a simple solution for expanding your network.

#### Auto-MDI/MDI-X

Every port can automatically sense your type of cable, so there is no need for crossover cables whether you are connecting this switch to another switch or to a computer.

#### Auto-Negotiation

Every port can automatically sense if the connected network devices are running at 10Mbps or 100Mbps and Half/Full-Duplex mode, and adjust accordingly.

#### Non-Blocking

This switch receives and forwards traffic seamlessly with its non-blocking wire-speed. Every port simultaneously supports up to 200Mbps of bandwidth in full-duplex mode. This feature provides full wire speed to the connected devices and allows you to run a smooth network.

#### Store and Forward

By this function, this switch can maximize network performance while minimizing the propagation of bad network packets.

#### Technical Specifications

<b>Standards</b>	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3x Flow Control
<b>Features</b>	Number of Ports: 8 MAC Address: 1K Buffer Memory: 512K bits Transmission Method: Store and Forward
<b>Filtering/Forwarding Rates</b>	100Mbps port - 148,800pps 10Mbps port - 14,880pps
<b>Transmission Media</b>	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP
<b>Led Indicators</b>	Per Port: Link/ACT Per Unit: Power
<b>Power Supply</b>	DC 5V/1.2A
<b>Power Consumption</b>	6 Watts (Max)
<b>Dimensions</b>	94 × 62 × 20 mm (L x W x H)
<b>Weight</b>	224 g
<b>Operating Temperature</b>	0 to 45°C
<b>Storage Temperature</b>	-20 to 90 °C
<b>Humidity</b>	10 to 90% RH (non-condensing)
<b>Certifications</b>	FCC Class B, CE