

EW-P72424iW

24-port 10/100M PoE + 2 Combo Gigabit Copper / 2 SFP Rack-mount Gigabit Ethernet Switch



- * **24-Port 10/100BaseT(X) PoE**
- * **2-Port Gigabit Copper and 2 SFP Open Slots**
- * **19" Industrial Size**
- * **IEEE 802.3at 30W (MAX) per port**
- * **Internal Power Supply**

Introduction

EW-P72424iW is 24-port 10/100M + 2 Combo Gigabit Copper / 2 SFP Rack-mount Gigabit Ethernet Switch that is designed for medium or large network environment to strengthen its network connection. Including rack-mount brackets, the 19" size fits into your rack environment. It is a superb choice to boost your network with better performance and efficiency.

2 Combo Gigabit Copper / 2 SFP Open Slots

EW-P72424iW supports 2 Combo Gigabit Copper or 2 SFP open slots to uplink to servers, storage, or other switching devices for long loop reach applications

Auto-MDI/MDI-X

Every port can automatically sense your type of cable, so there is no need for crossover cables whether you are connecting this switch to another switch or to a computer.

Auto-Negotiation

Every port can automatically sense if the connected network devices are running at 10Mbps, 100Mbps, or 1000Mbps and Half/Full-Duplex mode, and adjust accordingly.

Non-Blocking

This switch receives and forwards traffic seamlessly with its non-blocking wire-speed. Every port simultaneously supports up to 200 or 2000Mbps of bandwidth in full-duplex mode. This feature provides full wire speed to the connected devices and allows you to run a smooth network.

Store and Forward

By this function, this switch can maximize network performance while minimizing the propagation of bad network packets.

Specification

Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.ab 1000BaseT IEEE 802.3z 1000BaseSX/LX IEEE 802.3at PoE IEEE 802.3x Full-duplex and Flow Control
Features	Number of Ports: 10/100BaseTX with RJ-45 Connectors: 24 10/100/1000BaseT with RJ-45 Connectors: 2 Combo SFP Open Slots: 2 MAC Address: 4K Buffer Memory: 2.75Mb Transmission Method: Store and Forward
Filtering/Forwarding Rates	1000Mbps port – 1,488,000pps 100Mbps port - 148,800pps 10Mbps port - 14,880pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP
Led Indicators	Per Port: Link/Act Per Unit: Power
Power Requirement	90~260V/AC, 50~60Hz
Power Consumption	390 Watts (Max)
Dimensions	440 × 332 × 44 mm (L x W x H)
Weight	3.3 kg
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE